



## GOLDSTAR 2K ACRYTHANE CLEAR VARNISH

|                                 |   |
|---------------------------------|---|
| Type                            | : Two pack acrylic clear coat for interior use  |
| Salient Features                | : Cures to hard film with good adhesion and abrasion resistance ,good resistance to wide range of chemicals<br>good resistance to water     |
| Field of Application            | : To be used on doors , furniture , windows , wooden floors where good abrasion resistance is desired.                                      |
| <b>Technical Information:</b>   |   |
| Finish                          | : Gloss , Eggshell & Matt   |
| Colours / shades available      | : Clear and as per G.S wood coatings shade card   |
| Drying Time                     | : Surface dry 2-3 hrs , Hard Dry 24 hrs and 7 days for full cure  |
| % of solids                     | : 50 ± 2 %  |
| Coverage                        | : 8-10 m <sup>2</sup> / liter / coat, depending on surface  |
| Flash point                     | : Approx 24°C   |
| Specific gravity                | : 1.20 -1.22  |
| Thinner – for mixing & cleaning | : Acrythane thinner   |
| Surface preparation – Routine   | : Surface should be clean dry and any loose powder should be Removed. Applied over primed surface<br>Should not be used above 85 % humidity |
| Application                     | : Spray / Brush   |
| Packaging                       | : A+B: 4Lts + 2Lt (supplied in 1 Lt Pack size)  |
| Storage                         | : Store in a cool & dry place   |
| Shelf life                      | : 1 year  |
| Health & Safety                 | : Refer our Material Safety Data Sheet  |
| Precautions                     | : Keep the container closed after use. Do not intermix with Other Products<br>: Other references  |
| Mixing Ratio                    | : 2:1 by volume   |
| Pot life                        | : 5 hrs Maximum   |