



## GOLDSTAR 2K SUPACRYLIC

Type	: Two pack acrylic coating with U.V protection.
Salient Features	: Cures to hard film with good adhesion and abrasion resistance ,good resistance to wide range of chemicals good resistance to water
Field of Application	: To be used on doors , furniture , windows , wood, Concrete, plaster, ferrous metals, galvanized iron, aluminum etc. on appropriate primer.
<b>Technical Information:</b>	
Finish	: Gloss & Eggshell
Colours / shades available	: White, black and other colours on request.
Drying Time	: Surface dry 2-3 hrs , Hard Dry 24 hrs and 7 days for full cure
Solid Content	: 59.5 ± 2 %
Coverage	: 13-15 m <sup>2</sup> / liter / coat, depending on surface
Flash point	: Approx 24°C
Specific gravity	: 1.18 ± 0.02
Thinner – for mixing & cleaning	: Supacrylic slow thinner
Surface preparation – Routine	: Surface should be clean dry and any loose powder should be Removed. Applied on primed surface Should not be used above 85 % humidity
Application	: Spray / Brush
Packaging	: A+B: 4Lts 1Lt
Storage	: Store in a cool & dry place
Shelf life	: 1 year
Health & Safety	: Refer our Material Safety Data Sheet
Precautions	: Keep the container closed after use. Do not intermix with Other Products : Other references
Mixing Ratio	: 4:1 by volume
Pot life	: 5 hrs Maximum