



## GOLDSTAR DURASEAL G.P UNDERCOAT

- Type : GOLDSTAR DURASEAL G.P UNDERCOAT is a highly pigmented undercoat, based on an alkyd resin
- Salient Features : Excellent intermediate coat; Enhances the coverage and gloss hold out of the finishing enamel;
- Field of Application : Can be used on all types of wood, concrete, gypsum boards, ferrous & non ferrous, plaster etc over appropriate primers.

### Technical Information:

- Finish : Smooth Finish
- Colors/shades available : White
- Drying Time : Surface dry – 3 – 4 hrs, Hard dry – Overnight
- % of solids :  $65 \pm 2\%$
- Coverage : 8 – 10 m<sup>2</sup>/ liter/ coat, depending on surface
- Flash point : Above 38°C
- Specific gravity : 1.35 – 1.37
- Thinner – for mixing & cleaning : Goldstar G.P Thinner
- Surface Preparation – Routine : Ensure that the surface is clean, dry and free from all loose particles. If the surface is irregular, apply a coat of putty, sand it and cover with suitable primer.
- Application : Brush/Roller/Spray
- Packaging : 4 Liters.
- Storage : Store in a cool & dry place
- Shelf Life : 1 year
- Health & Safety : refer our Material Safety Data Sheet
- Precautions : Keep the container closed after use. Do not intermix with other products