



GOLDSTAR DURA DESIGN

Type:	Goldstar Dura Design is specially formulated for various designer's finishes for beautifying wall, wood or metal surfaces. This product is made with high quality latex binder for excellent feel & long lasting performance. It has very good anti-fungal and anti-algal properties which allows to apply on both interior and exterior surfaces. The combination of base coat and top coat gives attractive patterns such as leather, wood, comb, spatula and sisal finishes.
Salient Features:	Excellent Sheen, Wash-ability, Adhesion & Hardness
Field of Application:	can be applying by brush, roller, sponge, news paper and special tools for patterns like spatula, sisal etc.
Technical Information:	
Finish:	Silk finish
Color:	Un-limited (Depend on pattern)
Drying Time:	Touch dry: 4-6hrs, Hard dry: Over night
% Solids:	Base Coat: 35.00 +/- 2.00 & Top Coat: 23.00 ± 2.00%
Specific gravity (g/cm ³):	BASE COAT: 1.10 ± 2%. TOP COAT: 1.06 +/- 2%
Coverage:	BASE COAT: 12-14 Sq. Mt/ Lt / Coat. TOP COAT: 14-16 Sq. Mt/ Lt/ Coat
Ratio of Base & Top Coat:	Approx 4Lt : 1Lt
Thinning Ratio:	BASE COAT: 10-15% by volume. TOP COAT: 40-50% by volume.
Thinner:	Clean Water
Flash Point:	Non – flammable/ Not applicable
Surface Preparation:	Ensure that the surface is clean, dry and free from all loose powder.

Application:	BASE COAT: Apply 2-3 coats of desired color as base coat at the interval of 4-6 Hrs between two coats. TOP COAT APPLICATION: Apply desired top coat (single coat application) by selecting various tools to get desired patterns.
Packaging:	4Lt & 1Lt
Storage:	Store in a cool & dry place.
Shelf Life:	1 year.
Health & Safety:	Refer our Material safety data sheet.
Precautions:	Keep the container closed after use, Do not intermix with other products.

www.goldstarpaints.com