



---

## GOLDSTAR HOME GUARD INT/EXT

---

Type:	Goldstar Home Guard Int/Ext is based on an acrylic co-polymer with good durability
Salient Features:	Suitable for porous surfaces, Good penetration, and good water vapor permeability
Field of Application:	Home Guard can be used on interior / exterior various types of dry surfaces like plaster, concrete, building board, bricks, cement, stones for smooth finishes.

### **Technical Information:**

Finish:	Smooth finish
Color:	White and as per G.S Fan-decks
Drying Time:	Surface dry - 30minutes, Recoating - 4 hrs
% OF solids:	52±2% (For white & dark color) and 62±2% (For light pastel shades)
Coverage:	8 – 10m <sup>2</sup> / liter / coat depending of surface
Specific gravity (g/cm <sup>3</sup> ):	1.42 ± 2% (For white & dark color) and 1.57±2% (For light pastel shades)
Thinner for mixing:	Clean water, if is required
Flash Point:	Non - flammable
Surface Preparation:	Ensure that surface is clean, dry and free from all loose powder.
Packaging:	4ltr, 10ltr and 20ltr
Storage:	Store in a cool & dry place.
Shelf Life:	1 year.
Health & Safety:	Refer our Material safety data sheet.
Precautions:	Keep the container closed after use. Do not intermix with any other products.

---