



---

## GOLDSTAR INDUSTRIAL EPOXY ENAMEL

---

|                       |  |
|-----------------------|--|
| Type:                 | Goldstar Industrial Epoxy Enamel is a 2 pack Epoxy polyimide based top coat  |
| Salient Features:     | <p>Cures to very hard film with better adhesion and abrasion resistance.</p> <ul style="list-style-type: none"><li>⇒ Good resistance to wide range of chemical &amp; water. Good inter-coat adhesion</li><li>⇒ Easy to apply</li><li>⇒ Does not saponify</li></ul> |
| Field of Application: | To be used on Iron, Galvanized sheets, concrete where excellent inter-coat adhesion required for top coat.   |

### **Technical Information:**

|  |  |
|--|--|
| Finish:                                | Smooth Glossy  |
| Color:                                 | White & as per G.S Fandeck   |
| Drying time:                           | Surface Dry 1 – 3 hrs, Hard Dry – 24 hrs                                 |
| Specific gravity (g/cm <sup>3</sup> ): | 1.32 +/-0.02%  |
| Thinner:                               | Industrial Epoxy Thinner (For mixing & cleaning)                         |
| % Solids:                              | 61 ± 2%  |
| Coverage:                              | 10– 12m <sup>2</sup> / Liter / coat, depending on surface.               |
| Flash Point:                           | Approx. 21°C   |
| Pot life:                              | 6 – 8 hrs. Max   |
| Mixing ratio:                          | 4: 1 by volume (3.2L: 0.8L)  |
| Application:                           | Spray / Brush or Roller  |
| Surface Preparation:                   | Ensure that surface is clean, dry and free from all loose.               |
| Packaging:                             | A + B: 3.2Lts, 0.8Lt   |
| Storage:                               | Store in a cool & dry place.   |
| Shelf Life:                            | 1 year.  |
| Health & Safety:                       | Refer our Material safety data sheet.                                    |
| Precautions:                           | Keep the container closed after use. Do not intermix with other products |

---