

## 1 PRODUCT IDENTIFICATION AND COMPANY NAME

<b>Product Name</b>	: Goldstar NC Automotive Top Coat	<b>Contact</b>	: Rajesh Wagh
<b>Product Identification</b>	: Air drying NC based	<b>Tel</b>	: 255-22-2861677
<b>Supplier/Manufacturer</b>	: Gold Star Paints	<b>Fax</b>	: 255-22-2863005
<b>Address</b>	: 106 Mwakalinga Street Chang'ombe Dar Es Salaam Tanzania		

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Resin Base	:	NC	
Hazardous Components	:	Alcohol type solvents, NC resin	
Ethanol/IMS	<10%	CAS No 64-17-5	
Xylene	<10%		EC No 649-405-00-X
NC Resin	<10%	CAS no 9004-70-0	EC no 603-037-01-3
R Phrases		R11, 20/21/ 34/38/39/43/45/65	
S Phrases		S1/2. 13,26, 43, 45, 62	
Classification		Harmful, Xn	



## 3 HAZARDS IDENTIFICATION

<b>Physical/Chemical Hazards</b>	: This paint is FLAMMABLE-see above symbols
<b>Human Health Hazards</b>	: <i>Respiration</i> : May cause irritation, dizziness, nausea and loss of consciousness.
	: <i>Eyes</i> : May cause moderate irritation.
	: <i>Ingestion</i> : May cause gastro-intestinal irritation, dizziness, nausea and loss of consciousness.
	: <i>Skin</i> : May cause sensitization. May also be a skin irritant and repeated contact may increase this effect.
<b>Environmental Hazards</b>	: Toxic to aquatic organisms. May cause short-term adverse effects in the aquatic environment.

## 4 FIRST AID MEASURES

<b>General</b>	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	: Move to a safe area with fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by a trained person. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
<b>Eye Contact</b>	: Rinse thoroughly with potable water for at least 10 minutes.
<b>Ingestion</b>	: Do not induce vomiting. Keep person warm and at rest. Seek medical advice immediately and show this Safety Data Sheet to the medical officer.
<b>Skin Contact</b>	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use a recognized skin cleanser. Do not use solvents or thinners.

## 5 FIRE-FIGHTING MEASURES

- Extinguishing Media** : Use foam, CO<sub>2</sub>, dry powders and water mist. Do NOT use a high pressure water jet.
- Recommendations** : Decomposed products are a health hazard. Use appropriate breathing apparatus. Cool closed containers exposed to fire with water to prevent ignition.

## 6 ACCIDENTAL RELEASE MEASURES

- Personal Precautions** : Ventilate the area. Avoid breathing in vapours. Remove all sources of ignition e.g. flames, sparks, static electricity and heat.
- Spill** : Contain and collect spillage with absorbent material. Dispose of according to local regulations. Do not allow spillage to enter sewerage drains or watercourses.

## 7 HANDLING AND STORAGE

- Handling** : Keep container tightly closed. Keep away from heat, sparks and flame. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. After handling the material, workers should wash hands and face before eating, drinking and smoking. Always comply with health and safety regulations.
- Storage** : Store in original container. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from oxidizing agents, strong alkaline and acids. No smoking. Containers which have been opened must be carefully resealed and kept upright to prevent leakage.

## 8 EXPOSURE CONTROL/PERSONAL PROTECTION

- Engineering Measures** : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.
- Personal Protective Equipment** :
- Respiration* : Should ventilation be inadequate or if workers are exposed to concentrations above the exposure limit, appropriate certified respirators must be used.
  - Eyes* : Use safety eyewear designed to protect against splash of liquids. Never touch eyes with dirty hands or gloves.
  - Ingestion* : Observe the rules of hygiene. Wash hands and face before eating, drinking or smoking.
  - Skin* : Use protective gloves. Wash immediately in case of contact.
- Environmental Exposure Control** : Do not allow product to enter sewerage drains or watercourses.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : High viscosity Liquid
- Flash Point (°C)** : Above 4 °C
- Solubility** : Alcohols

## 10 STABILITY AND REACTIVITY

- Stability** : Stable under recommended storage and handling conditions.
- Conditions to Avoid** : Ignition sources, flames, sparks, static and heat.
- Materials to Avoid** : Oxidizing agents, strong alkaline or acidic materials.

## 11 TOXICOLOGICAL INFORMATION

- Frequent and prolonged skin contact may cause irritation and skin inflammation.
- Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.
- In case of contact with the product, danger of absorption through the skin, irritation of the skin/mucous membranes.

## 12 ECOLOGICAL INFORMATION

- There is no data available on the preparation itself.
- Product is considered a water pollutant. Do not allow to enter drains or watercourses.

## 13 DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose according to state and local applicable regulations.
- Empty containers are suitable for recycling.

## 14 TRANSPORT INFORMATION

Not classified as dangerous for transport.

## 15 REGULATORY INFORMATION

Classification: Harmful, Xn

- R11                Highly Flammable  
R20/21           Harmful by inhalation and contact with the skin  
R34                Causes Burns  
R38                Irritating to the skin  
R39                Danger of very serious Irreversible effects  
R43                May Cause Sensitization by Skin Contact  
R45                May Cause Cancer  
R65                Harmful- may cause lung damage if swallowed  
S1/2:             Keep locked up/ out of reach of Children  
S13                Keep away from food, drink and animal feed stuffs  
S24/25           Avoid Contact with Skin/eyes  
S43                In case of fire, use water, fog, foam or powder-do not use water jets  
S62                If swallowed, do not induce vomiting but seek medical advice  
                      Immediately

## 16 OTHER INFORMATION

- Date of Printing** : November 2013  
**Date of Issue** : November 2013  
**Version** : 1  
**Notice** : The information in this MSDS is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the product's properties.



## SAFETY DATA SHEET

DATA SHEET NO. WF004/09

---

[www.goldstarpaints.com](http://www.goldstarpaints.com)