

# **SAFETY DATA SHEET**

DATA SHEET NO. WF004/09

#### 1 PRODUCT IDENTIFICATION AND COMPANY NAME

Product Name
Product Identification
Supplier/Manufacturer

Air drying NC based ClearGold Star Paints

Address

: 106 Mwakalinga Street

Gold Star NC Lacquer/Stain

Chang'ombe Dar Es Salaam Tanzania Contact : Rajesh Wagh

Tel

Fax

: 255-22-2861677 : 255-22-2863005

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Resin Base : NC

Hazardous Components : Alcohol type solvents, NC resin

Ethanol/IMS <10% CAS No 64-17-5

Xylene <10% EC No 649-405-00-X NC Resin <10% CAS no 9004-70-0 EC no 603-037-01-3

R Phrases R11. 20/21/

34/38/39/43/45/65 S1/2. 13,26, 43, 45, 62

Classification Harmful, Xn



S Phrases



#### 3 HAZARDS IDENTIFICATION

Physical/Chemical Hazards : This pai Human Health Hazards : Respira

: This paint is FLAMMABLE-see above symbols

: Respiration : May cause irritation, dizziness, nausea and

loss of consciousness.

Eyes: May cause moderate irritation.

Ingestion : May cause gastro-intestinal irritation, dizziness,

nausea and loss of consciousness.

Skin : May cause sensitization. May also be a skin

irritant and repeated contact may increase this

effect.

**Environmental Hazards**: Toxic to aquatic organisms. May cause short-term adverse effects

in the aquatic environment.

### 4 FIRST AID MEASURES

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never

give anything by mouth to an unconscious person.

**Inhalation**: Move to a safe area with fresh air. Keep person warm and at rest. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by a trained person. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

**Eye Contact** : Rinse thoroughly with potable water for at least 10 minutes.

**Ingestion**: Do not induce vomiting. Keep person warm and at rest. Seek medical advice

immediately and show this Safety Data Sheet to the medical officer.

Skin Contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use a recognized skin cleanser. Do not use solvents or thinners.



# **SAFETY DATA SHEET**

DATA SHEET NO. WF004/09

#### 5 FIRE-FIGHTING MEASURES

Extinguishing Media : Use foam, CO2, dry powders and water mist. Do NOT use a high

pressure water jet.

**Recommendations**: Decomposed products are a health hazard. Use appropriate breathing

apparatus. Cool closed containers exposed to fire with water to prevent

ignition.

### 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions : Ventilate the area. Avoid breathing in vapours. Remove all sources of

ignition e.g. flames, sparks, static electricity and heat.

**Spill** : Contain and collect spillage with absorbent material. Dispose of

according to local regulations. Do not allow spillage to enter sewerage

drains or watercourses.

#### 7 HANDLING AND STORAGE

**Handling**: Keep container tightly closed. Keep away from heat, sparks and flame.

Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. After handling the material, workers should

wash hands and face before eating, drinking and smoking.

Always comply with health and safety regulations.

Storage : Store in original container. Observe label precautions. Store in a cool, well-

ventilated area away from incompatible materials and ignition sources.

Keep away from oxidizing agents, strong alkaline and acids.

No smoking. Containers which have been opened must be carefully resealed

and kept upright to prevent leakage.

#### 8 EXPOSURE CONTROL/PERSONAL PROTECTION

**Engineering Measures** : Provide adequate ventilation. Where reasonably practicable

this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory

protection must be worn.

Personal Protective Equipment :

Ingestion

Respiration : Should ventilation be inadequate or if workers are exposed

to concentrations above the exposure limit, appropriate

certified respirators must be used.

Eyes : Use safety eyewear designed to protect against splash of liquids. Never tough eyes with dirty hands or gloves.

: Observe the rules of hygiene. Wash hands and face before

. Observe the rules of hygiene. Wash hands and race before

eating, drinking or smoking.

Skin : Use protective gloves. Wash immediately in case of

contact.

**Environmental Exposure Control**: Do not allow product to enter sewerage drains or

watercourses.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Low viscosity Liquid

Flash Point (°C) : Above 4 °C Solubility : Alcohols

#### 10 STABLILTY AND REACTIVITY

**Stability** : Stable under recommended storage and handling conditions.

Conditions to Avoid : Ignition sources, flames, sparks, static and heat.

Materials to Avoid : Oxidizing agents, strong alkaline or acidic materials.



# **SAFETY DATA SHEET**

DATA SHEET NO. WF004/09

#### 11 TOXICOLOGICAL INFORMATION

- Frequent and prolonged skin contact may cause irritation and skin inflammation.
- Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.
- In case of contact with the product, danger of absorption through the skin, irritation of the skin/mucous membranes.

#### 12 ECOLOGICAL INFORMATION

- There is no data available on the preparation itself.
- Product is considered a water pollutant. Do not allow to enter drains or watercourses.

#### 13 DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose according to state and local applicable regulations.
- · Empty containers are suitable for recycling.

#### 14 TRANSPORT INFORMATION

Not classified as dangerous for transport.

#### 15 REGULATORY INFORMATION

Classification: Harmful, Xn

R11 Highly Flammable

R20/21 Harmful by inhalation and contact with the skin

R34 Causes Burns

R38 Irritating to the skin

R39 Danger of very serious Irreversible effects R43 May Cause Sensitization by Skin Contact

R45 May Cause Cancer

R65 Harmful- may cause lung damage if swallowed

S1/2: Keep locked up/out of reach of Children

S13 Keep away from food, drink and animal feed stuffs

S24/25 Avoid Contact with Skin/eyes

In case of fire, use water, fog, foam or powder-do not use water jets

S62 If swallowed, do not induce vomiting but seek medical advice

**Immediately** 

#### 16 OTHER INFORMATION

Date of Printing : March 2008
Date if Issue : March 2008

Version : 2

Notice : The information in this MSDS is based on the present state of our

knowledge and on current national laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the product's properties.