



GOLD STAR POLYACRYTHANE FLOOR COATING

- Type : GOLDSTAR POLYACRYTHANE is a two pack acrylic Isocyanate floor paint
- Salient Features : Cures to a hard film with good adhesion and abrasion resistance with gloss , Good resistance to wide range of chemicals ,solvents and water
- Field of Application : Can be applied to external floor areas which requires frequent cleaning with solvents or detergents offering clean surroundings in hospitals, factories, breweries, bulk storage factories where abrasion resistance is required.

TECHNICAL INFORMATION

- Finish : Glossy
- Colours/shades available : Clear /Eggshell /Matt
- Drying Time : Surface dry 2-4 hrs, Hard dry : 24 hrs, Full cure 7 days
Recoating minimum 6 hrs , max 72 liters.
- Coverage : 8-10 m²/ liter depending on the wood
- Solids : 49 ± 2 %
- Specific gravity : 1.20 – 1.22
- Flash point : 24 deg c
- Thinner – for mixing & clearing :Goldstar Acrythane thinner
- Mixing Ratio :2 parts Base Lacquer Clear,
1 part Hardener 1part Thinner
- Pot Life : 8 hrs at 25°C
- Surface Preparation –Routine : Surface should clean, dry and free from oil, dust and
Other impurities
- Application : Spray (conventional, airless, curtain)
- Packaging : 4liters
- Storage : Store in a cool and dry place
- Shelf Life : 1 year
- Health & Safety : refer our Material Safety Data Sheet
- Precautions : Keep the container closed after use. Do not intermix
other products