

GOLDSTAR ROADMARKING PAINT

| Туре | : | GOLDSTAR ROAD MARKING PAINT is a hard wearing quick drying Paint |
|---------------------------------|------------|--|
| Salient Features | : | Excellent weather resistance; Scratch resistant; |
| Field of Application | : | Can be used on all Bitumen roads, concrete and plaster surfaces |
| Technical Information: | | |
| Gloss | : | Semi Gloss 🛇 |
| Finish | : | Smooth |
| Colour/shades available | : | White, yellow, black. |
| Drying Time | : | Surface dry 15 min – 20min , Hard Dry – 1 Hr. |
| % of solids | : | 72 ±2 % |
| Coverage | : | 8 – 10 m2 / liter depending on shade |
| Flash point | : | Approx 25°C |
| Specific gravity | : | 1.42 1.44 |
| Thinner – for mixing & cleaning | ((| Road marking Thinner |
| Surface Preparation – Routine | | Surface should be clean, dry and any loose powder |
| | | should be removed. |
| Application | ∖ . | Spray/Roller/Brush |
| Packaging | : | 4 Liters / 200 Liters |
| Storage | : | Store in a cool & dry place |
| Shelf Life | : | l year. |
| Health & Safety | : | Refer our Material Safety Data Sheet. |
| Precautions | : | Keep the container closed after use. Do not intermix |
| | | with other products. |
| | | |