



---

## **GOLDSTAR SPARKLING ALUMINIUM /SILVER PAINT**

---

Type:	Goldstar Sparklig Aluminium / Silver Paint is formulated using special resin & aluminum pigment
Salient Features:	Protects against UV rays; Withstands temperatures upto 100°C; has good luster.
Field of Application:	Can be used indoors and outdoors on iron, steel and other metals after an appropriate primer. In certain cases, it can also be used for sealing against penetration – e.g. on asphalted surfaces.

### **Technical Information:**

Appearance:	Lustrous
Finish:	Smooth Finish
Colours/shades available:	Aluminium
Drying Time:	Surface dry – 1 hrs, hard dry overnight
% of solids:	46 ± 2 %
Coverage:	12 – 15 m <sup>2</sup> / litre, depending on surface
Flash point:	Above 38°C
Specific gravity:	0.90 - 0.92
Thinner-for mixing & cleaning:	Brushing – Goldstar G.P Thinner Spraying – Goldstar G.P Thinner
Surface Preparation – Routine:	Surface should be clean, dry and any loose powder should be removed.
Application:	Brush/Spray
Packaging:	4 Liters
Storage:	Store in a cool & dry place
Shelf Life:	1 year
Health & Safety:	Consult our Material Safety Data Sheet
Precautions:	Keep the container closed after use. Do not intermix with other products

---