



---

## GOLDSTAR STANDARD GLOSS ALUMINIUM PAINT

---

Type:	Goldstar Standard Gloss Aluminium Paint is designed based on alkyd resin & aluminium pigment
Salient Features:	Good moisture and salt spray resistance Good heat reflectance, High opacity, obliterating qualities easy to apply
Field of Application:	Can be used indoors and outdoors on iron, steel and other metals after an appropriate primer. Provides good resistance to damp conditions and salt water.

### Technical Information:

Appearance:	Lustrous
Finish:	Smooth Finish
Colours/shades available:	Aluminium
Drying Time:	Surface dry – 1 hr, Hard dry 16 – 18 hrs
% of solids:	43 ± 2 %
Coverage:	12 -15 m <sup>2</sup> / liter, depending on surface
Flash point:	Above 43°C
Specific gravity:	0.89 - 0.91
Thinner-for mixing & cleaning:	Brushing – Goldstar G.P Thinner Spraying –Goldstar G.P Thinner
Surface Preparation – Routine:	Surface should be clean, dry and any loose powder should be removed.
Application:	Brush/Spray
Packaging:	4 LTS.
Storage:	Store in a cool & dry place
Shelf Life:	1 years
Health & Safety:	Refer our Material Safety Data Sheet
Precautions:	Keep the container closed after use. Do not intermix with other products .

---