

SAFETY DATA SHEET

DATA SHEET NO. WF005/09

	DATA SHEET NU. WFUUJ/U9
1 PRODUCT IDEN	TIFICATION AND COMPANY NAME
Product Name Product Identificatio Supplier/Manufactur Address	
2 COMPOSITION/	NFORMATION ON INGREDIENTS
Resin Base Hazardous Componen Ethanol/IMS Xylene PTSA R Phrases S Phrases Classification	 UF modified Alkyd Alcohol type solvents, PTSA CAS No 64-17-5 CAS no 6192-52-5 CAS no 6192-52-5 EC no R11, 20/21/ 34/38/39/43/45/65 S1/2. 13,26, 43, 45, 62 Harmful, Xn
3 HAZARDS IDEN	
Physical/Chemical H Human Health Hazar Environmental Hazar	ds: Respiration: May cause irritation, dizziness, nausea and loss of consciousness.Eyes: May cause moderate irritation.Ingestion: May cause gastro-intestinal irritation, dizziness, nausea and loss of consciousness.Skin: May cause sensitization. May also be a skin irritant and repeated contact may increase this effect.
4 FIRST AID MEA	
General : In	all cases of doubt, or when symptoms persist, seek medical attention. Never ve anything by mouth to an unconscious person.
Inhalation : M br re UI Eye Contact : R Ingestion : D im Skin Contact : R	ove to a safe area with fresh air. Keep person warm and at rest. If not eathing, if breathing is irregular or if respiratory arrest occurs, provide artificial spiration or oxygen by a trained person. Give nothing by mouth. If noonscious, place in recovery position and seek medical advice. Inse thoroughly with potable water for at least 10 minutes. To not induce vomiting. Keep person warm and at rest. Seek medical advice mediately and show this Safety Data Sheet to the medical officer. The move contaminated clothing and shoes. Wash skin thoroughly with soap and ater or use a recognized skin cleanser. Do not use solvents or thinners.



5 FIRE-FIGHTING MEASURES		
Recommendations : Deci appa ignit		
6 ACCIDENTAL RELEASE N	IEASURES	
ignit Spill : Con acco	tilate the area. Avoid breathing in vapours. Remove all sources of ion e.g. flames, sparks, static electricity and heat. tain and collect spillage with absorbent material. Dispose of ording to local regulations. Do not allow spillage to enter sewerage as or watercourses.	
7 HANDLING AND STORAG	E	
Eating, dri is handled wash hand Always co Storage : Store in or ventilated Keep away No smokin	ainer tightly closed. Keep away from heat, sparks and flame. hking and smoking should be prohibited in area where this material stored and processed. After handling the material, workers should ls and face before eating, drinking and smoking. mply with health and safety regulations. iginal container. Observe label precautions. Store in a cool, well- area away from incompatible materials and ignition sources. y from oxidizing agents, strong alkaline and acids. 19. Containers which have been opened must be carefully resealed pright to prevent leakage.	
8 EXPOSURE CONTROL/PE	RSONAL PROTECTION	
Engineering Measures	: Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.	
Personal Protective Equipment :		
Respiration Eyes Ingestion	 Should ventilation be inadequate or if workers are exposed to concentrations above the exposure limit, appropriate certified respirators must be used. Use safety eyewear designed to protect against splash of liquids. Never tough eyes with dirty hands or gloves. Observe the rules of hygiene. Wash hands and face before eating, drinking or smoking. 	
Skin	: Use protective gloves. Wash immediately in case of contact.	
Environmental Exposure Cont		
9 PHYSICAL AND CHEMICAL PROPERTIES		
Flash Point (°C) :	Low viscosity Liquid Above 4 ºC Alcohols	
10 STABLILTY AND REACTIVITY		
Stability : Conditions to Avoid : Materials to Avoid :	Stable under recommended storage and handling conditions. Ignition sources, flames, sparks, static and heat. Oxidizing agents, strong alkaline or acidic materials.	
Cold Ctox Turbohvight	Borro O of O	



SAFETY DATA SHEET

11 TOXICOLOGICAL INFORMATION

- Frequent and prolonged skin contact may cause irritation and skin inflammation.
- Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.
- In case of contact with the product, danger of absorption through the skin, irritation of the skin/mucous membranes.

12 ECOLOGICAL INFORMATION

- There is no data available on the preparation itself.
- Product is considered a water pollutant. Do not allow to enter drains or watercourses.

13 DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose according to state and local applicable regulations.
- Empty containers are suitable for recycling.

14 TRANSPORT INFORMATION

Not classified as dangerous for transport.

15 REGULATORY INFORMATION

Classification: Harmful, Xn

R11	Highly Flammable	
R20/21	Harmful by inhalation and contact with the skin	
R34	Causes Burns	
R38	Irritating to the skin	
R39	Danger of very serious Irreversible effects	
R43	May Cause Sensitization by Skin Contact	
R45	May Cause Cancer	
R65	Harmful- may cause lung damage if swallowed	
S1/2:	Keep locked up/ out of reach of Children	
S13	Keep away from food, drink and animal feed stuffs	
S24/25	Avoid Contact with Skin/eyes	
S43	In case of fire, use water, fog, foam or powder-do not use water jets	
S62	If swallowed, do not induce vomiting but seek medical advice	
	Immediately	

16 OTHER INFORMATION		
Date of Printing Date if Issue Version Notice	 March 2008 March 2008 2 The information in this MSDS is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the product's properties. 	