



## GOLD STAR TURBOBRIGHT

Type	: GOLDSTAR TURBOBRIGHT is a clear / tinted is a fast drying 2 component acid – catalyzed interior furniture lacquer
Salient Features	: Hard wearing; High Slip and scratch resistance; Quick drying;
Field of Application	: Can be used on bare timber and timber stained with a low build wood stain which has dried properly. It can also be used on all wooden Surfaces where an extremely high degree of durability is required

### Technical Information:

Finish	: Glossy , Egg shell and Matt
Colors/shades available	: Clear & other shades as per GS wood coating chart
Drying Time	: Touch dry 15-20min, Recoating 1-2 hrs
Solid content	: $43 \pm 2 \%$
Specific gravity	: 0.90 – 0.92
Coverage	: 6-8 SQ.M per LT.
Flash point	: 4 deg c
Thinner-for mixing & cleaning	: Clean brush/roller immediately with Gold Star standard economy thinner
Surface Preparation-Routine	: Surface should be clean, dry and any loose powder should be removed. If the surface has been Previously painted, remove all paint and treat as new wood.
Application	: Brush / Mohair Roller / Spray
Packaging	: 4 LTS
Storage	: Store in a cool and dry place
Shelf Life	: 1 year
Health & Safety	: refer our Material Safety Data Sheet
Precautions	: Keep the container closed after use. Do not intermix with other products.
Mixing Ratio	: 4 % CATALYT BY VOLUME
Pot Life	: 24hrs in closed container