



## **GOLDSTAR WATER REPELLANT SILICON SOLUTION**

Type	: GOLDSTAR WATER REPELLANT SILICON SOLUTION is a low viscous product which penetrates into substrates and dries to a high water repellent coating.
Salient features	: High water repellency within 24 hrs. Minimizes dirt accumulation Dries to a invisible film
Field of Application	: Suitable for direct application on brick , tile , concrete, cement , asbestos and other porous siliceous material can also be top coated on conventional emulsion or enamel paint Not suitable for limestone , gypsum or proofing of textiles or water tanks where high hydrostatic pressure is experienced.

### **Technical Information**

Finish	: Smooth
Colours	: Clear
Drying Time	: Surface dry - 2 hrs , recoating 2 hrs
Coverage	: 2-4 m <sup>2</sup> / liter / coat, depending on surface
Flash point	: Above 37°C
Specific gravity	: 0.79-0.81
Thinner – for mixing & cleaning	: Supplied ready to use
Surface Preparation – Routine	: To be applied on bare concrete surface.
Packaging	: 4 Liter
Storage	: Store in a cool & dry place
Shelf life	: 1 year
Health & Safety	: Refer our Material Safety Data Sheet
Precautions	: Keep the container closed after use. Do not intermix with other products.