



## GOLDSTAR WEATHERGUARD

Type	: GOLDSTAR WEATHERGUARD acrylic emulsion is based on premium quality acrylic polymer offering very good exterior durability
Salient Features	: Especially suitable for coastal areas. Hard wearing & long lasting Low odor and quick drying Prevents fungal growth
Field of Application	: Weatherguard can be used on variety of surfaces  like plaster, concrete, Hardboard, bricks, soft and hard board as well as on wood with appropriate primer.
<b>Technical Information</b>	
Finish	: Smooth finish
Colours / shades available	: White and as per GS color Fandeck
Drying time	: Surface dry – 30 minutes, Recoating – 4 hrs
% of solids	: 46 ± 2 %
Coverage	: 12 – 15 m <sup>2</sup> / litre, depending on surface
Flash point	: Non – Flammable
Specific gravity	: 1.26 -1.28
Thinner – for mixing & cleaning	: Clean water, if required
Surface Preparation – Routine	: Surface should be clean, dry and free from any loose powder should Be removed apply suitable primer.
Application	: By Roller / Brush
Packaging	: 4 LTS / 20LTS
Storage	: Store in a cool & dry place
Shelf life	: 1 year
Health & Safety	: refer our Material Safety Data Sheet
Precautions	: Keep the container closed after use. Do not intermix with other product